



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

UV BLACK CABLE TIES TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

F4P Black Cable Ties are UV-resistant for outdoor use and plenum rated. A wide variety of sizes and tensile strength combinations are available to fit any need. The design of F4P pawl (locking mechanism) makes our cable ties superior in strength and allows our products to exceed the required tensile strength by margins of 3 to 4 times greater than industry standards.



PHYSICAL SPECIFICATIONS

Color: Black

STANDARDS & SPECIFICATIONS

UL Reference - # E336321

UV Light Resistant - Yes

Type: 2, 21



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

ORDERING INFORMATION

PART	STOCK CODE	TYPE	LENGTH	WIDTH	THICKNESS	DIAMETER	STRENGTH	PACK QTY.	CASE QTY.
F4P04-18B	0276-9300	Miniature	4.12"	0.09"	0.04"	0.87"	18 LB	100	10,000
F4P05-40B	0276-9306	Intermediate	5.84"	0.14"	0.04"	1.43"	40 LB	100	10,000
F4P06-18B	0276-9312	Miniature	6.18"	0.09"	0.04"	1.50"	18 LB	100	10,000
F4P07-50B	0276-9318	Standard	7.56"	0.18"	0.05"	1.87"	50 LB	100	10,000
F4P07-50B-M	0276-9321	Standard	7.56"	0.18"	0.05"	1.87"	50 LB	1000	10,000
F4P08-120B	0276-9336	Heavy Duty	8.70"	0.30"	0.07"	2.0"	120 LB	100	3000
F4P11-50B	0276-9342	Standard	11.25"	0.18"	0.05"	3.06"	50 LB	100	5000
F4P11-50B-M	0276-9345	Standard	11.25"	0.18"	0.05"	3.06"	50 LB	500	5000
F4P14-50B	0276-9366	Standard	14.56"	0.18"	0.05"	4.12"	50 LB	100	5000
F4P14-120B	0276-9354	Heavy Duty	15.09"	0.30"	0.07"	4.06"	120 LB	100	2000
F4P17-50B	0276-9372	Standard	17.09"	0.18"	0.06"	4.75"	50 LB	100	5000
F4P24-175B	0276-9378	Extra Heavy Duty	25.25"	0.34"	0.09"	7.18"	175 LB	50	500
F4P36-175B	0276-9408	Extra Heavy Duty	37.25"	0.34"	0.09"	11.00"	175 LB	50	500
F4P48-175B	0276-9411	Extra Heavy Duty	48.56"	0.34"	0.09"	14.50"	175 LB	50	500

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: f4p-usa.com

CUSTOMER SERVICE: 772-408-5211

DISCLAIMER

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies. No other warranties apply, including fitness for a particular purpose.