

| PART NUMBER: | DATE: |
|--------------|-------|
| PROJECT #: | TYPE: |
| PREPARED BY: | |

F4P DUCT TAPE PRO TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

F4P duct tape is a uniquely soft, high-strength, high-tack adhesive that readily flows across rough and textured surfaces. The improved adhesive is even stronger than ever, providing 20% more shear strength (holding power) than before – perfect for hanging poly sheeting and other demanding applications.



FEATURES -

- Conforms well to irregular surfaces
- High adhesion
- Resists twisting and curling

- Tested in accordance with UL 723
- Low VOC

APPLICATIONS —

- Heavy-duty repair and maintenance
- Duct and vent sealing applications
- Waterproof packaging
- Media-blast protection

PHYSICAL SPECIFICATIONS

Total Thickness: 0.47 in (12 mm)
Total Length: 60.1 yds (55 m)

Backing: PE Coated Cloth

Color: Gray

Adhesive: Rubber

PERFORMANCE SPECIFICATIONS

Tensile Strength: $24 \, \text{lb/in} \, (42.03 \, \text{N/cm})$ Adhesion to Steel: $70 \, \text{oz/in}$ Operating Temperature: $40^\circ \, \text{to} \, 200^\circ \, \text{F}$ VOC Content: $<1 \, \text{g/L}$

(4° to 93° C)

Tested: In accordance with UL 723

Recommended Storage Conditions: 32° to 90° F at 50% RH \pm 2%

Standard Shelf Life (at 77°F (25°C)): 36 months from date of manufacture



| PART NUMBER: | DATE: |
|--------------|-------|
| PROJECT #: | TYPE: |
| PREPARED BY: | |

ORDERING INFORMATION

| PART NUMBER | STOCK CODE | TAPE WIDTH |
|-------------------|------------|-----------------|
| F4P DUCT TAPE PRO | 0312-9864 | 1.89 IN (48 MM) |

Data represents average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use. Application and Performance Specification Information is Subject to Change Without Notification.

MSDS/EDS/PRODUCT DATA SHEETS: f4p-usa.com CUSTOMER SERVICE: 772-878-4944

DISCLAIMER -

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies. No other warranties apply, including fitness for a particular purpose.